



Atlanta, Georgia

Phone 800-521-7326

Fax 770-745-1333

Nylon Cable Ties

MADE IN THE USA (Items Marked With "*" Are Made In Taiwan)

Miniature Cable Ties - 18 LB Tensile Strength - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Thickness	Minimum		Maximum		Material	Mil-Spec Reference	UL Information			Unit	Catalog Page
					Bundle Dia	Bundle Dia	Temp	Temp			Listed	Air Handling Approved	Flame Rating		
AL-04-18-0-C	705591000278	4.12"	0.09"	0.04"	0.06"	0.87"	-40 F	185 F	UV Black Nylon	MS3367-4-0				100	7-2
AL-04-18-0-M	705591000186	4.12"	0.09"	0.04"	0.06"	0.87"	-40 F	185 F	UV Black Nylon	MS3367-4-0	UL Listed Type 21	UL AH-2	94V-2	1000	7-2
AL-04-18-9-C	705591000339	4.12"	0.09"	0.04"	0.06"	0.87"	-40 F	185 F	Natural Nylon	MS3367-4-9				100	7-2
AL-04-18-9-M	705591000247	4.12"	0.09"	0.04"	0.06"	0.87"	-40 F	185 F	Natural Nylon	MS3367-4-9				1000	7-2

Standard Cable Ties - 50 LB Tensile Strength - RoHS Compliant - CSA Certified**

Peco Catalog#	UPC	Length	Width	Thickness	Minimum		Maximum		Material	Mil-Spec Reference	UL Information			Unit	Catalog Page
					Bundle Dia	Bundle Dia	Temp	Temp			Listed	Air Handling Approved	Flame Rating		
AL-07-50-0-C	705591005587	7.56"	0.18"	0.05"	0.06"	1.87"	-40 F	185 F	UV Black Nylon	MS3367-1-0				100	7-2
AL-07-50-0-M	705591005495	7.56"	0.18"	0.05"	0.06"	1.87"	-40 F	185 F	UV Black Nylon	MS3367-1-0				1000	7-2
AL-07-50-9-C	705591005648	7.56"	0.18"	0.05"	0.06"	1.87"	-40 F	185 F	Natural Nylon	MS3367-1-9				100	7-2
AL-07-50-9-M	705591005556	7.56"	0.18"	0.05"	0.06"	1.87"	-40 F	185 F	Natural Nylon	MS3367-1-9				1000	7-2
AL-11-50-0-C	705591006874	11.25"	0.18"	0.05"	0.06"	3.06"	-40 F	185 F	UV Black Nylon	MS3367-7-0				100	7-2
AL-11-50-0-D	705591006782	11.25"	0.18"	0.05"	0.06"	3.06"	-40 F	185 F	UV Black Nylon	MS3367-7-0				500	7-2
AL-11-50-9-C	705591006935	11.25"	0.18"	0.05"	0.06"	3.06"	-40 F	185 F	Natural Nylon	MS3367-7-9	UL Listed Type 21	UL AH-2	94V-2	100	7-2
AL-11-50-9-D	705591006843	11.25"	0.18"	0.05"	0.06"	3.06"	-40 F	185 F	Natural Nylon	MS3367-7-9				500	7-2
AL-14-50-0-C	705591008106	14.25"	0.18"	0.05"	0.06"	4.00"	-40 F	185 F	UV Black Nylon	MS3367-2-0				100	7-2
AL-14-50-0-D	705591008014	14.25"	0.18"	0.05"	0.06"	4.00"	-40 F	185 F	UV Black Nylon	MS3367-2-0				500	7-2
AL-14-50-9-C	705591007987	14.25"	0.18"	0.05"	0.06"	4.00"	-40 F	185 F	Natural Nylon	MS3367-2-9				100	7-2
AL-14-50-9-D	705591008076	14.25"	0.18"	0.05"	0.06"	4.00"	-40 F	185 F	Natural Nylon	MS3367-2-9				500	7-2
AL-17-50-0-C*	705591009219	17.09"	0.18"	0.05"	0.27"	4.52"	-40 F	185 F	UV Black Nylon					100	7-2
AL-17-50-9-C*	705591009240	17.09"	0.18"	0.05"	0.27"	4.52"	-40 F	185 F	Natural Nylon					100	7-2

** The new 2017 National Electrical Code (NEC) now permits UL Type 21S certified cable ties to be used as supporting devices in electrical installations. Type 21S Supporting Device classification certifies products for their suitability in providing primary support for flexible conduits, tubing, and cables in accordance with the maximum spacing intervals when specified in the relevant national installation codes, such as the 2017 National Electrical Code (NEC) and the 2015 Canadian Electrical Code (CEC). Peco cable ties are Type21S certified for 50 lb. and 120 lb. Natural, Burgundy, Colors, and UV Black cable ties.

Heavy Duty Cable Ties - 120 LB Tensile Strength - RoHS Compliant - CSA Certified**

Peco Catalog#	UPC	Length	Width	Thickness	Minimum		Maximum		Material	Mil-Spec Reference	UL Information			Unit	Catalog Page
					Bundle Dia	Bundle Dia	Temp	Temp			Listed	Air Handling Approved	Flame Rating		
AL-08-120-0-C	705591009363	8.70"	0.30"	.076"	0.19"	2.06"	-40 F	185 F	UV Black Nylon		UL Listed Type 21	UL AH-2	94V-2	100	7-2
AL-08-120-9-C	705591009424	8.70"	0.30"	.076"	0.19"	2.06"	-40 F	185 F	Natural Nylon					100	7-2
AL-14-120-0-C	705591009639	15.09"	0.30"	.076"	0.19"	4.06"	-40 F	185 F	UV Black Nylon	MS3367-3-0	UL Listed Type 21	UL AH-2	94V-2	100	7-2
AL-14-120-9-C	705591009721	15.09"	0.30"	.076"	0.19"	4.06"	-40 F	185 F	Natural Nylon	MS3367-3-9	UL Listed Type 21	UL AH-2	94V-2	100	7-2
AL-18-120-0-L	705591010321	18.25"	0.30"	.083"	0.19"	5.00"	-40 F	185 F	UV Black Nylon		UL Listed Type 21	UL AH-2	94V-2	50	7-2
AL-18-120-9-L	705591010291	18.25"	0.30"	.083"	0.19"	5.00"	-40 F	185 F	Natural Nylon		UL Listed Type 21	UL AH-2	94V-2	50	7-2

** The new 2017 National Electrical Code (NEC) now permits UL Type 21S certified cable ties to be used as supporting devices in electrical installations. Type 21S Supporting Device classification certifies products for their suitability in providing primary support for flexible conduits, tubing, and cables in accordance with the maximum spacing intervals when specified in the relevant national installation codes, such as the 2017 National Electrical Code (NEC) and the 2015 Canadian Electrical Code (CEC). Peco cable ties are Type21S certified for 50 lb. and 120 lb. Natural, Burgundy, Colors, and UV Black cable ties.

Heavy Duty Cable Ties - 175 LB Tensile Strength - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Thickness	Minimum		Maximum		Material	Mil-Spec Reference	UL Information			Unit	Catalog Page
					Bundle Dia	Bundle Dia	Temp	Temp			Listed	Air Handling Approved	Flame Rating		
AL-24-175-0-L	705591010741	25.25"	0.34"	0.09"	1.50"	7.18"	-40 F	185 F	UV Black Nylon	MS3367-10-0	UL Listed		94V-2	50	7-2
AL-24-175-9-L	705591010802	25.25"	0.34"	0.09"	1.50"	7.18"	-40 F	185 F	Natural Nylon	MS3367-10-9	181B-C & Type 21	UL AH-2	94V-2	50	7-2
AL-36-175-0-L	705591011229	37.25"	0.34"	0.09"	1.50"	11.00"	-40 F	185 F	UV Black Nylon	MS3367-13-0				50	7-2
AL-36-175-9-L	705591011281	37.25"	0.34"	0.09"	1.50"	11.00"	-40 F	185 F	Natural Nylon	MS3367-13-9				50	7-2

Mounting Hole Cable Ties - 50 LB Tensile Strength - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Thickness	Minimum		Maximum		Material	Hole Screw Size	UL Information			Unit	Catalog Page
					Bundle Dia	Bundle Dia	Temp	Temp			Listed	Air Handling Approved	Flame Rating		
AL-07-50-MH-0-C	705591012073	8.00"	0.17"	0.05"	0.06"	1.75"	-40 F	185 F	UV Black Nylon	#10 Screw	UL		94V-2	100	7-3
AL-07-50-MH-0-M	705591012110	8.00"	0.17"	0.05"	0.06"	1.75"	-40 F	185 F	UV Black Nylon	#10 Screw	Recognized			1000	7-3
AL-07-50-MH-9-C	705591012097	8.00"	0.17"	0.05"	0.06"	1.75"	-40 F	185 F	Natural Nylon	#10 Screw				100	7-3

Adhesive Mounting Pads - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Thickness	Slot		Mechanical Maximum		Material	Hole Screw Size	UL Information			Unit	Catalog Page
					Width	Height	Strength	Temp			Listed	Air Handling Approved	Flame Rating		
AL-MP-1000-0-C	705591015890	0.99"	0.99"	0.20"	0.20"	0.06"	11 LBS	158 F	UV Black Nylon	#6 Screw	UL		94V-2	100	7-3
AL-MP-1000-9-C	705591015937	0.99"	0.99"	0.20"	0.20"	0.06"	11 LBS	158 F	Natural Nylon	#6 Screw	Recognized			100	7-3
AL-MP-750-0-C	705591018594	0.74"	0.74"	0.20"	0.20"	0.06"	11 LBS	158 F	UV Black Nylon	#4 Screw	Type 11			100	7-3

Call Peco For Any Of Your Cable Tie Needs
 Air Handling - Beaded Ties - Low Profile - Cold Weather - Colors - Double Head
 Heat Stabilized - Identification - Metal Detectable - Push Mount - Releasable
 Our Cable Ties Are Now Air Handling Approved Now By UL