


Atlanta, Georgia

Phone 800-521-7326

Fax 770-745-1333

Flat Washer USS Grade 8 Yellow Zinc



Peco		Inside Diameter			Outside Diameter			Thickness		Appoximate
Catalog#	Bolt Size	Nominal	Min	Max	Nominal	Min	Max	Min	Max	Quantity in 50 Lbs.
	1/4	5/16	0.307	0.327	3/4	.727	0.749	0.055	0.072	7500
	5/16	3/8	0.370	0.390	7/8	.868	0.905	0.064	0.080	5000
	3/8	7/16	0.433	0.453	1	0.993	1.030	0.064	0.080	3500
	7/16	1/2	0.495	0.515	1-1/4	1.243	1.280	0.064	0.080	2500
	1/2	9/16	0.557	0.577	1-3/8	1.368	1.405	0.097	0.121	1500
Please see	9/16	5/8	0.620	0.640	1-1/2	1.462	1.499	0.097	0.121	1100
section five in	5/8	11/16	0.681	0.718	1-3/4	1.743	1.780	0.122	0.146	700
our catalog.	3/4	13/16	0.805	0.842	2	1.993	2.030	0.122	0.146	500
	7/8	15/16	0.931	0.968	2-1/4	2.243	2.280	0.136	0.160	350
	1	1-1/16	1.055	1.092	2-1/2	2.493	2.530	0.136	0.160	300
	1-1/8	1-1/4	1.243	1.280	2-3/4	2.743	2.780	0.136	0.160	250
	1-1/4	1-3/8	1.368	1.405	3	2.993	3.030	0.136	0.160	200
	1-1/2	1-5/8	1.615	1.670	3-1/2	3.490	3.545	0.136	0.160	150
Material	SAE 1035 - 1050 Steel									
Hardness	Rockwell C38 - 45									
	ANSI B18	221								

Peco Fasteners specification sheets are a reference guide to help in the selection of fasteners. Peco has made every effort to ensure the accuracy of the information. However, Peco Fasteners is not responsible for any errors that may be contained within these sheets. Peco Fasteners makes no claim of warranty in the accuracy of this information. Users of this information are solely responsible for protecting themselves against liability. It is solely the responsibility of the purchasers and users of these fasteners to consult with Engineers that are experts in an applicable field. Peco Fasteners is not responsible for any loss, claim, or damage due to these specification sheets.